



Note:-

- 1) Wiring to be in accordance with current IEE regulations
- 2) Refer also to the fitting and wiring instructions for the fans and controllers

Control description:-

Sentinel Kinetic switching from trickle to Boost by two lighting circuits, or Trickle/Boost switch.

B	xxxx	2-2-2010	S.R.A.
A	XXXX	28.1.2010	STAU
ISSUE	MOD	DATE	CHK'D

ORIGINAL DRAWING SIZE A3	ALL DIMENSIONS IN MILLIMETRES TOLERANCES UNLESS OTHERWISE SPECIFIED:- ±0.5 ON NOMINAL DIMENSIONS ±0.2 ON 1 DECIMAL PLACE DIMENSIONS ±0.1 ON 2 DECIMAL PLACE DIMENSIONS ±0.1 ON HOLE DIAMETERS ETC ±1.0 DEGREE ON ANGULAR DIMENSIONS	This drawing/document is COPYRIGHT and the property of VENT-AXIA Ltd. It must not be copied (in whole or in part), used for manufacture or otherwise disclosed without prior written consent of the company. Any copies of this drawing/document made by any method must also include a copy of this legend. © VENT-AXIA Ltd. 2002	DRAWN DGIBSON	DATE 28.1.2010	CHK'D	DATE	TITLE	
			MATERIAL -				Wiring Diagram Sentinel Kinetic two Light Sw & Trickle/boost Sw	
			FINISH -					PART No
			PRODUCT	SCALE -				DRG 443766 B
					PROJECTION			