

Silhouette® 150

Axial Kitchen Fans



Features & Benefits

- Stylish ultra low profile grille.
- Downstream airflow guide vanes for improved pressure development.
- Modern aesthetics.
- Electric back draught shutters.
- IPX4 rated.
- Suitable for wall, ceiling and panel mounting.
- Meets Building Regulations Part F

Slimline Kitchen Ventilation

The Silhouette range is designed for modern living. With a profile of only 19mm on the kitchen models, Silhouette blends in with the wall surface to provide an unobtrusive installation.

Mounted in the centre of the fan, beneath the ultra slim profile grille, are the electronics, incorporating a humidistat for detecting a change in internal humidity or an overrun timer option that is adjustable between 5 and 30 mins.

Models

Silhouette 150mm models - Slim profile only 19mm. FID performance of 241m³/h, double insulated.

Silhouette 150X



Single speed 150mm kitchen fan with neon running light and electric back draught shutter.

Stock Ref
454059A

Silhouette 150XT



Single speed 150mm kitchen fan with integral adjustable electronic overrun timer (up to 30 mins), neon running light and electric backdraught shutter.

Stock Ref
454060A

Silhouette 150XH



Single speed 150mm with integral adjustable auto humidity sensor from 60-90% RH, neon running light and electric backdraught shutter. Switch live for override by remote switch/light switch.



Stock Ref
454061A

Dimensions (mm)


A	B	C	D	G	H
223	147	111	19	220	37

Weight 1.75kg

Panel



Wall



Fixing hole diameter 152mmØ
(when wall kit used)

Wall Kit Stock Ref:
254102 (White)
254100 (Brown)

Performance

Model	Extract Performance - FID			Sound dB(A) @ 3m
	m³/h	l/s	Watts	
Silhouette 150X	241	67	20	43
Silhouette 150XT	241	67	20	43
Silhouette 150XH	241	67	20	43