

Traditional T-Series® Wall Models



Features & Benefits

- Extract/intake model in 4 sizes: 6, 7, 9 and 12.
- Patented electronic shutter system ensures quiet, trouble free operation.
- Designed to comply with International safety standards.
- For the very best from your fan use the Ecotronic controller.
- Easy fit connector Top Socket, standard on all models.

UK's No. 1 Commercial Fan

Behind the grille of the Vent-Axia T-Series Wall model is a range of high performance extract/intake ventilating units designed to fit through most wall thicknesses using telescopic liners supplied.

T-Series also features a unique speed control pack which enables high, medium or low speed to be preset to suit room size or required duty.

T-Series controllers may be used with this model to obtain a choice of speeds, reversible airflow direction and automatic sensor operation. The Vent-Axia Ecotronic controller gives even greater running economy with its minimum speed setting and 'E' mode.

Performance

Model	Extract performance m ³ /h (l/s)			Watts (high)	Sound dB(A) (med) @ 3m	Amps @ 240V
	low	medium	high			
TX6WL	270 (75)	350 (97)	395 (110)	30	43	0.24
TX7WL	335 (93)	435 (120)	530 (147)	40	39	0.24
TX9WL	515 (143)	755 (210)	870 (241)	85	43	0.42
TX12WL	1185 (329)	1530 (425)	1745 (485)	105	49	0.51

For further performance details please go to www.vent-axia.com

Top Socket

A connector Top Socket is now standard on all T-Series fans. Allowing fast and trouble-free mains connection.

Shutter

TX models are supplied complete with an integral instantaneous automatic louvre shutter which will operate on both intake and extract and at any angle of mounting.

When the ventilating unit is used with a T-Series controller, the shutter can be set open with the fan motor switched off to provide natural ventilation without the security risk of an open window.

Electrical

Motor purpose-designed. Suitable for running at any angle. Quiet running, enclosed. Suitable for operation in ambient temperatures from -40°C to +50°C.

Fitted with self resetting Standard Thermal Overload Protection (S.T.O.P.).

Supply voltage 220-240V/1/50Hz.

Models

Wall Models

Designed to fit into most double brick walls using the telescopic liners, supplied. Additional liners are available to accommodate exceptional brick walls.

Model	Stock Ref
TX6WL	W161510B
TX7WL	W162510B
TX9WL	W163510B
TX12WL	W164510B

Dimensions (mm)

Size Dim.	6 mm	7 mm	9 mm	12 mm
A	310	352	391	470
B	303	345	388	467
C	290	330	365	442
D	290	330	375	450
E	104	124	143	182
Weight kg	5.54	6.13	7.77	10.86

