

Hand Dryers



Tempest

GEN

Automatic hand dryer for heavy duty applications - 10-15 second drying time.

- Unique "blue dry zone" indicator
- Cover: Steel. Finish porcelain enamel coating
- Insulation Earthed Class 1
- 201 x 277 x 175 (WxHxD)
- Weight 6.6kg (packaged)
- Air flow 116m³/h
- Heater Element 450-900W, adjustable
- Infrared automatic operation
- 60 second auto shut off
- **IPX1** rated



Turbodry Chrome Auto

GEN

Automatic hand & face dryer for heavy duty applications where a robust secure design is required.

- Cover: Steel. Chrome
- Insulation Earthed Class 1
- 248 x 284 x 202 (HxWxD)
- Weight 7.5kg
- Sound level 70dB(A) @1m
- Rated at 2.4kW @ 230 V
- **IP23** Rated



Turbodry White Auto

GEN

Automatic hand & face dryer for heavy duty applications where a robust secure design is required.

- Cover: Steel. Finish porcelain enamel coating
- Insulation Earthed Class 1
- 248 x 284 x 202 (HxWxD)
- Weight 7.5kg
- Sound level 70dB(A) @1m
- Rated at 2.4kW @ 230 V
- **IP23** Rated



Powerdry SX

GEN

Push button operated hand and face dryer for heavy duty applications in public lavatories, factories, railway stations and schools, etc. Fast drying feature.

- Cover: LM24 pressure die cast aluminium. Finish: epoxy/polyester powder coating. Motor: 5,500rpm, suppressed brushed motor. Insulation: earthed, Class 1.
- 264 x 275 x 177mm (H x W x D).
- Weight: 6.0kg (6.6kg packed).
- Sound level: 79dB(A) at 1m.
- Rated at: 2.4kW at 230V.
- **IP24** Rated.
- BEAB Approved.
- Supply voltage: 220-240V/1/50-60Hz



Prepdry-Stainless Steel

GEN

Designed for food preparation areas and hospital applications where the highest levels of hygiene have to be observed. Automatic 'no-touch' hand dryer. BEAB Approved.

- Cover: Satin polished stainless steel.
- Motor: External Rotor Brushless Motor 2700 rpm. Insulation: earthed Class 1.
- 280 x 270 x 148mm (H x W x D).
- Weight: 4.0kg (4.5kg packed).
- Sound level: 65 dB(A) at 1m.
- Rated at: 2.0 kW at 240V.
- Supply voltage: 220-240V/1/50Hz.



Dryline +

GEN

Automatic 'no-touch' operation compact hand dryer. Suitable for smaller office washrooms, kitchens and clinics.

- Cover: ABS. Motor: 2450rpm shaded pole induction.
- Double insulated appliance.
- BEAB approved.
- 280 x 275 x 143mm (H x W x D).
- Weight: 2.97kg (3.3kg packed).
- Sound level: 46 dB(A) at 3m.
- Rated at: 1.7kW at 230V.
- Supply voltage: 220-240V/1/50Hz.



Turbodry White Manual

GEN

Push button hand & face dryer for heavy duty applications where a robust secure design is required.

- Cover: Steel. Finish porcelain enamel coating
- Insulation Earthed Class 1
- 248 x 284 x 202 (HxWxD)
- Weight 7.5kg
- Sound level 70dB(A) @1m
- Rated at 2.4kW @ 230 V
- **IP23** Rated



Ultradry SX Stainless Steel

GEN

Automatic 'no-touch' hand dryer specially designed for high performance hand drying in food preparation areas and hospital applications and eminently suitable for prestige installations. Fast drying feature. BEAB Approved.

- Cover: Satin polished stainless steel.
- 264 x 275 x 177mm (H x W x D).
- Weight: 6.0kg (6.6kg packed).
- Sound level: 79dB(A) at 1m.
- Rated at: 2.4kW at 230V.



Ultradry SX

GEN

Automatic 'no-touch', vandal resistant hand and face dryer for offices, shops, restaurants, pubs, clubs and hospitals. Fast drying feature.

- Cover: LM24 pressure die cast aluminium. Finish: epoxy/polyester powder coating. Motor: 5,500rpm, suppressed brushed motor. Insulation: earthed, Class 1.
- 264 x 275 x 177mm (H x W x D).
- Weight: 6.0kg (6.6kg packed).
- Sound level: 79dB(A) at 1m.
- Rated at: 2.4kW at 230V.
- **IP24** Rated.
- BEAB Approved.



Professional E

GEN

Automatic 'no-touch' hand dryer for smaller office washrooms, kitchens and clinics.

- Cover and base: high gloss, fire retardant ABS/polycarbonate alloy. Motor: 2700rpm external rotor, brushless motor.
- Double insulated appliance.
- 262 x 261 x 141mm (H x W x D).
- Weight: 3.09kg (3.52kg packed).
- Sound level: 65 dB(A) at 1m.
- Rated at: 2.0 kW at 240V.
- **IP24** Rated.
- BEAB Approved.
- Supply voltage: 220-240V/1/50Hz



Easy Dry Range

GEN

An economical ABS or Metal covered automatic dryer, designed for use in applications where good performance linked with price sensitivity is of paramount importance. S/GS Approved.

- 2500 rpm induction motor
- Insulation: Earthed Class 1.
- 275 x 225 x 160mm (H x W x D).
- Weight: 3.3kg (3.65kg packed), 4.7kg (5.5kg packed)
- Sound levels: 54dB(A) at 1m
- Rated at: 1.0kW, 1.5kW or 2kW at 240V.
- **IP22** Rated.
- Supply voltage: 220-240V/1/50Hz

