




N.B.
PURGE VIA CONTROL ON
FAN UNIT OR OPTIONAL
WIRELESS CONTROLLER

LOGIC BOARD										SENTINEL KINETIC CONTACT									
S/W1	S/W2	S/W3	SW4	SW5	P1 0-10V	P2 0-10V	LED												
+	-	+	-	+	-	+	-	+	-	S	-	+	S	-	+	-			


MAINS
SUPPLY
220/240V 50Hz



3 POLE
LOCAL ISOLATOR



REMOTE ROOM SWITCH
USING COOKER HOOD LS
WHEN ACTIVE, BYPASS OPEN



Note:-

- 1) Wiring to be in accordance with current IEE regulations
- 2) Refer also to the fitting and wiring instructions for the fans and controllers

Control description :-

Sentinel Kinetic switching from trickle to Boost by a light switch or Purge by Remote Room Switch using cooker hood LS.

ORIGINAL DRAWING SIZE A3

ALL DIMENSIONS IN MILLIMETRES
TOLERANCES UNLESS OTHERWISE SPECIFIED:-
±0.5 ON NOMINAL DIMENSIONS
±0.2 ON 1 DECIMAL PLACE DIMENSIONS
±0.1 ON 2 DECIMAL PLACE DIMENSIONS
±0.1 ON HOLE DIAMETERS ETC
±1.0 DEGREE ON ANGULAR DIMENSIONS

This drawing/document is COPYRIGHT and the property of VOLUTION VENTILATION GROUP.
It must not be copied (in whole or in part), used for manufacture or otherwise disclosed without prior written consent of the company.
Any copies of this drawing/document made by any method must also include a copy of this legend.
© VOLUTION VENTILATION GROUP 2017

DRAWN G.S.WILSON	DATE 08.02.18	ISSUE A	INITIAL	08.02.18	M.C.	08.02.18	GSW
MATERIAL -		MOD			CHK'D		
FINISH -							
PRODUCT -	SCALE N.T.S.						
		PRODUCTION			PART No -	DRG 478044	A
				TITLE WIRING DIAGRAM SENTINEL KINETIC - LIGHT SWITCH & REMOTE SWITCH USING C.H. LD			