

# Fast Dry Hand Dryers



## Jet Dry® Plus

Automatic double sided, high speed dryer, for high traffic settings.

- 99.9% HEPA filter
- UV sterilisation
- 10 second drying time
- LED indicator
- Removable drip tray
- Air speed 95m/s
- Low carbon DC motor, as low as 750W to 2050W
- Heater element 900W - 1300W, adjustable on/off
- 700 x 300 x 225mm (H x W x D)
- Weight 9.5kg
- IPX4 rated
- Sound level: 75dB(A) at 1m
- Cable entry bottom right
- Three-year warranty
- Ambient temperature response element
- Antibacterial coating
- GS approved

Models  
Silver

Stock Ref  
409117



## Jet Dry® Junior

Automatic double sided, high speed dryer, for low traffic settings.

- 99.9% HEPA filter
- UV Sterilisation
- 10-12 second drying time
- LED indicator
- Removable drip tray
- Air speed 150m/s
- Brushed motor, as low as 1250W to 1650W
- Heater element 400W adjustable on/off
- 671 x 279 x 195mm (H x W x D)
- Weight 8.8kg
- IP23 rated
- Sound level: 75dB(A) at 1m
- Cable entry bottom right
- Two-year warranty

Models  
Silver

Stock Ref  
497992



## Tempest® - Reduced Sound

Automatic no-touch hand dryer for heavy duty applications.

- 10 second drying time
- Air speed: 75-100 m/s, adjustable
- Infrared automatic operation
- Unique blue dry zone indicator
- Automatically senses work surfaces to avoid nuisance running
- Cover: Steel. Finish: Polished or satin stainless steel
- Insulation Earthed Class 1
- Heater element 450 - 900W, adjustable on/off
- Rated at 500W - 1.6kW at 230V
- Weight 6.6kg (packaged)
- 277 x 201 x 175mm (H x W x D)
- 60 second auto shut off
- Soft start
- IP23 rated
- GS approved
- Cable entry bottom left
- Motor: Max 18,000rpm brushed motor
- Motor speed adjustable
- Sound level: reduced to 72dB(A) at 1m

Models

Stock Ref

Satin Stainless	439464
Polished Stainless	439463
White	437231
Filter Assembly Pack	444959
Filter Replacement 2 pack	444960



## Lo-Carbon eTempest

Automatic hand dryer for fast drying applications.

- 10 second drying time
- Air speed: 52-90 m/s, adjustable
- Infrared automatic operation
- Unique blue dry zone indicator
- Automatically senses work surfaces to avoid nuisance running
- Cover: Steel 1.2 mm thick, epoxy coated
- Insulation Earthed Class 1
- Heater element 500W adjustable on/off
- Rated at 500kW - 1.2 kW at 230V
- Weight: 3.8Kg
- 180 x 250 x 138.5mm (H x W x D)
- 60 seconds auto shut off
- Soft start
- IPX1 rated
- GS approved
- Cable entry bottom left
- Motor: Max 30,000rpm brushed motor

Model  
White

Stock Ref  
444956

