

Fire Stopping


Vent-Axia provides a complete range of fire stopping products specifically tested with ventilation ducting. This versatile selection allows for stacking and parallel installation in certain circumstances, along with creative solutions for partition walls and slab mounting. All Fire Sleeves provide 120 minutes Integrity & Insulation. Fire Rated diffusers are tested successfully to 60 minutes.

Please note: For installations above 18m for England / Wales and NI and 11m for Scotland, all external grilles/parts used within the system must comply with BSEN13501-1:2018.



Fire Rated Diffuser

Duct Size	Extract Stock Ref	Supply Stock Ref
100 Ø	403431	475661
125 Ø	403432	475662
150 Ø	403433	475663
200 Ø	408828	475664



Round Fire Sleeve - Low profile

Thickness:	10-15mm	
Length:	280mm (180mm	407655)
CE Marked		
Duct Size		Stock Ref
100mm		407655
125mm		407656
150mm		407657



Rectangular Fire sleeve - Low profile - 4 sided

Thickness:	10-15mm	
Length:	180mm	
CE Marked		
Duct Size		Stock Ref
110x54mm		407658
204x60mm		407659
220x90mm		407660



Ceiling Fan Fire Stop

For ceiling breaks only

Model


100mmØ Fire Collar - 30 min fire-rated

125mmØ Fire Collar - 30 min fire-rated

Stock Ref

435134

435135



Round Fire Sleeve

Model

Round 100mm sleeve

Round 125mm sleeve


Round 150mm sleeve

Stock Ref

403428

403429

403430



Rectangular Fire sleeve

Model

Rectangular 204x60mm sleeve - 3 sided

Rectangular 204x60mm wrap

Stock Ref

403498

435138

Fire Sleeves are tested & approved to:

BS EN 1366-3: 2009 - Uncapped/Uncapped (U/U) Constructions = Plasterboard & Masonry Walls

Fire Rating: EI120 (120 mins Integrity & Insulation)

Report No.'s: RF13219A, RF12096, RF10167, IF11007, IF10066, IF05055, IF06016, / Chiltern Int. Fire PAR/11078/01-IFC Assessment Report

Fire Rated Diffusers successfully tested for 60 minutes according to BS EN 1365-2:1999 Test Report Number: BTC 18074F & CHILT/IF10090

Fire Test Assessment also covers multiple flat ducts to be installed in series / side by side, max. 3No., 30, 60 & 120 Minute Partitions, Single & Double Boards.

Note: For a copy of the Fire Certificates for the product(s) above, visit our webpage www.vent-axia.com/range/ventilation-fire-stopping.