

Name:
Model ID (Stock Ref.) :
SEC Class
SEC Value ('Average')
SEC Value ('Warm')
SEC Value ('Cold')
Label Required? (Yes/No=Out of scope)
Declared as: RVU or NRVU/UVU or BVU
Speed Drive
Type HRS (Recuperative, Regenerative, None)
Thermal Eff: [ (%), NA(if none)]
Max. Flow Rate (m3/h)
Max. Power Input (W): (@Max.Flow Rate)
LWA: Sound Power Level (dB)
Ref. Flow Rate (m3/s)
Ref. Pressure Diff. (Pa)
SPI [W/(m3/h)]
Control Factor & Control Typology: (CTRL/ Typology)
Control Factor; CTRL
Control Typology
Declared: -Max Internal & External Leakage Rates(%) for BVUs or carry over (for regenerative heat exchangers only), -&Ext. Leakage Rates (%) for Ducted UVUs;
Mixing Rate of Non-Ducted BVUs not intended to be equipped with one duct connection on either supply or extract air side;
Position and description of visual filter warning for RVUs intended for use with filters, including text pointing out the importance of regular filter changes for performance and energy efficiency of the unit
For UVUs (Instructions Install Regulated Supply/Extract Grilles Façade)
Internet Address (for Disassembly Instructions)
Sensitivity p. Variation@+20/-20 Pa: (for Non-Ducted VUs)
Air Tightness-ID/OD-(m3/h) (for Non-Ducted VUs)
Annual Electricity Consumption: AEC (kWh/a)
Annual Heating Saved: AHS (kWh/a)
AHS: Average
AHS: Warm
AHS: Cold

Vent-Axia
Kinetic Plus E - 449059
A+
-43.44
-17.84
-88.91
Yes
RVU/BVU
Variable Speed
Recuperative
93
417.6
190
57.33
0.081
50
0.28
0.65
Local Demand Control
<5% Internal, <5% External
N/A
Refer to User Instructions
N/A
<a href="http://www.vent-axia.com">www.vent-axia.com</a>
N./A
N./A
1.92
47.56
21.50
93.03